## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

01232695

**PUBLICATION DATE** 

18-09-89

APPLICATION DATE

11-03-88

APPLICATION NUMBER

63058748

APPLICANT:

MATSUSHITA ELECTRIC IND CO LTD;

INVENTOR:

ABE ATSUSHI;


INT.CL.

H05B 33/22 G09F 9/30

TITLE

THIN FILM ELECTROLUMINESCENT

**ELEMENT** 



ABSTRACT :

PURPOSE: To make adhesion between thin films good and let luminescence characteristics maintained stably for a long period by composing a dielectric layer of a composite thin film of AIN to which BN is added.

CONSTITUTION: A thin film of indium-tin mixed crystal oxide is formed on a glass substrate 1 by sputtering and processed into stripes by photo-etching to be a transparent electrode 2. A first layer of dielectric 3 is formed on it by sputtering consisting of AIN solely or AIN including BM, and a fluorescent thin film 4 of ZnS:Mn is formed by EB deposition. A second layer of dielectric 5 is then formed in the completely similar method to that for the layer 3, and finally a back electrode 6 of AI is applied by EB deposition, which are then processed to be perpendicular stripes to the electrode 2. A thin film electroluminescent element having a good peeling resistance, good withstand voltage characteristics and extremely small fluctuation of luminescence threshold voltage in drive for a long time can thus be manufactured at a good yield.

COPYRIGHT: (C)1989,JPO&Japio